

> PRINT

# ECOSYS P8060cdn

COLOUR PRINTER FOR A3 FORMAT





Our new high-end A3 colour printer is the perfect choice for demanding workgroups and production offices. With a print speed of up to 60 A4 pages per minute for b/w and 55 for colour, the device's new colour technology offers outstanding and vivid results and our new printer offers a maximum paper capacity of 7,150 sheets. Its fast performance is secured by an 8 GB Solid State Drive and a 320 GB HDD, enabling it to maintain its high print speeds even at maximum print resolution. Additionally, the redesigned 9" touch panel makes accessing all features very intuitive and easy to use.

- > Up to 60/55 pages per minute A4 in b/w and colour
- > Outstanding image quality due to advanced colour technology
- > Standard print resolution of 1,200 x 1,200 dpi, 2 bit depth (equivalent of 4,800 x 1,200 dpi)
- > Advanced paper handling from A6 up to SRA3 and beyond for up to 7,150 sheets
- > 4 GB RAM, 8 GB SSD + 320 GB HDD memory and storage
- > Long-life components providing exceptional efficiency and reliability, and less waste
- > HyPAS capable to run KYOCERA business applications for printing





ECOSYS stands for ECOlogy, ECOnomy and SYStem-printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that toner is the only consumable. The modular design concept allows you to add workflow enhancing functions as required. Integrated system software provides long-term cross network compatibility. KYOCERA's long-life components cost you and the environment less.

### **ENVIROMENTAL PRINT FEATURES**

Duplex print mode (Double sided printing), N-Up printing mode (N pages on 1 sheet), Toner save mode (Draft print mode).

## KYOCERA NetViewe

KYOCERA NetViewer enables complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunction units from any Windows® PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

# COMMAND CENTER RX

The Command Center RX enables to control and manage various settings by accessing the device via Web browser.

## USB HOST INTERFACE FOR USB FLASH MEMORY

Documents can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. The documents stored as PDF, XPS, TIFF or JPEG are selected directly via the printer's control panel. No computer is required.

## APPLICATION-BASED PROFILES

The KX printer driver can create a direct link between dedicated applications and predefined or customised print profiles. You can set that all documents from a user or an application be printed in b/w with activated duplex mode as standard, thus leading to a reduced toner and paper consumption.

#### **GENERAL**

Technology: KYOCERA ECOSYS, Colour Laser Touch panel size: 22.8 cm (9 inch) full-colour touch panel display, 15° – 90° swivel mounted Engine speed (pages per minute): Up to 55/27 ppm A4/A3 in colour, up to 60/30 A4/A3 in b/w

Resolution: 1,200 x 1,200 dpi, 2 bit depth for print quality of 4,800 dpi equivalent x 1,200 dpi

Warm-up time from power on: Approx. 13 seconds or less

Time to first page: Approx. 3.8 sec. or less in b/w; 5.1 sec. or less in colour CPU: Freescale QorlQ T1024 (Dual Core) 1.2 GHz

Memory (standard max.): 4 GB RAM, 8 GB SSD

Standard interface: 4x USB 2.0 (Hi-Speed), USB Host 2.0, Fast Ethernet 10 BaseT/100 BaseTX/1,000 BaseT, slot for rast Enteriet to basel full obserts, full to optional print server, slot for optional SD card Dimensions (W x D x H): Main unit: 602 x 665 x 790 mm Weight: Main unit approx. 89 kg Power source: AC 220 V ~ 240 V, 50/60 Hz

Printing: 960 W (in colour and b/w)
Ready mode: 60 W

Sleep mode: 1 W or less

Sleep mode: 1 W or less
Noise (sound pressure level ISO 7779/ISO 9296):
Printing monochrome: 55.4 dB(A) LpA
Printing in colour: 55.5 dB(A) LpA
Ready mode: 19.0 dB(A) LpA
Safety standards: TÜV - GS, CE.
This unit is manufactured according to ISO 9001 quality
standard and ISO 14001 environmental standard.
Rolls compatibility. RoHs compatibility

Average continuous toner yield in accordance with ISO/IEC 19798

ISO/IEC 19798

Toner-Kit TK-8800K: black toner yield 30,000 pages A4 Starter toner: black toner yield 15,000 pages A4
Toner-Kit TK-8800C, TK-8800M, TK-8800Y: cyan, magenta, yellow toner yield 20,000 pages A4 Starter toner: cyan, magenta, yellow toner yield 10,000

WT-8500 Waste Toner Bottle: 40,000 sheets or more (in accordance with ISO/IEC 19798, ratio b/w:colour = 7:3)

Staple cartridge: SH-10 for DF-7120, BF-730 SH-12 for DF-7110

### PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended KYOCERA under normal environmental conditions Input capacity:

The state  $(3.6 \pm 0.00)$  is the state  $(3.6 \pm 0.00)$  in the state  $(3.6 \pm 0.00)$  is  $(3.6 \pm 0.00)$  in the state  $(3.6 \pm 0.00)$  in the state upper cassette A6R up to A4R, lower cassette A6R up to SRA3, Max. input capacity with options: 7,150 sheets A4

Duplex unit: Duplex as standard supports A6R – SRA3 (320 x 450 mm), 64 – 256 g/m² **Output capacity:** Standard 500 sheets face-down, max. output capacity with options 4,300 sheets

#### PRINT FUNCTIONS

Controller language: PRESCRIBE Emulations: PCL6 (PCL5c / PCL-XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and OpenXPS Operating systems: All current Windows operating systems, Mac OS X Version 10.8 or higher, UNIX LINUX,

as well as other operating systems on request
Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL3),
8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes plus two-dimensional

of one-dimensional barcodes plus two-uniterisional barcode (PDF-417) **Print features:** Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, private print, job storage and job management functionality **Mobile printing support:** KYOCERA Mobile Print app for iOS and Android; AirPrint, Mopria, NFC, Direct Wi-Fi, Google/Loud Print GoogleCloud Print

**PF-7100 Paper feeder:** 2x 500 sheets,  $52-300 \text{ g/m}^2$ , A6R-SRA3 (320 x 450 mm), folio **PF-7110 Paper feeder:** 2x 1,500 sheets, 52 – 300 g/m², **PF-7120 A4 side Deck:** 3,000 sheets, 60 – 300 g/m², A4, B5 (PF-7100 or PF-7110 required) IS-7100 lob separator: CB-7100 No separator.
100-sheet internal job separator, 52 – 300 g/m², A5R – SRA3
CB-7100W: Wooden cabinet
CB-7110M: Metal cabinet

DF-7110\* Document finisher + AK-7100:

Main tray: Max. 4,000 sheets A4 (3,000 sheets with attachment BF-730); max. 52 – 300 g/m²; max. AGR – SRA3 Sub tray: 200 sheets A4; 52 – 300 g/m²; AGR – SRA3 AK -7100: 100 sheets; 52 – 300 g/m²; AGR – SRA3 Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions,

B5-5NA3
DF-7320\* Document finisher + AK-7100:
Main tray: 1,000 sheets A4, 52-300 g/m², A6R - SRA3, 3 positions stapling up to 50 sheets A4 or 30 sheets SRA3
AK-7100: 100 sheets; 52-300 g/m², A6R - SRA3, 'Bridge unit AK-7100 is required for the use of DF-7110 and DF-7120.

and Dr-7120.

PH-7C/PH-7D Punch unit for DF-7120/DF-7110:

2-hole/4-hole/Swedish type, 60 – 300 g/m², A5R – A3

MT-730(B) Mailbox sorter for DF-7110:

7 bins x 100 sheets A4, 50 sheets A3/B4, 60 – 165 g/m²

BF-730 Booklet and tri-folding unit for DF-7110

Half-folding: 52 – 256 g/m², A3, B4, A4R

Booklet: Max. 16 sheets (64 pages, 60 – 90 g/m²)

Non-staple folding: May r sheets (66 – 00 g/m²) Non-staple folding: Max. 5 sheets  $(60 - 90 \text{ g/m}^2)$ Tri-folding:  $60 - 105 \text{ g/m}^2$ , A4R Multi tri-folding: 5 sheets  $(60 - 90 \text{ g/m}^2)$ , 3 sheets

(91–105 g/m²)

Data security kit (E): In line with ISO 15408
(common criteria) with security level EAL3

NK-7100 Numeric keypad (91-105 g/m<sup>2</sup>)

USB IC Card Reader: Card Authentication Kit (B)AC UG-33: ThinPrint support
UG-34: Emulation (IBM Proprinter/EPSON LQ-850/

Optional interface

IB-35: Direct Wi-Fi Interface IB-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/ 1,000 BaseT

IR-E1: Wireless I AN Interface

ECOSYS P806ocdn/KL3: ECOSYS P806ocdn incl. warranty extension KYOlife 3 years

# WARRANTY

1-year warranty\*\* as standard. KYOCERA guarantees the drum and developer for 3 years or maximum 600,000 pages
A4 (whichever occurs sooner), provided the printer is used
and cleaned in accordance with the service instructions.



The up to 5-year on-site warranty extension for printer and options.













KYOCERA Document Solutions South Africa 90 Bekker Road, Hertford Office Park, Vorna Valley, Midrand Tel (011) 595 2600 www.kyoceradocumentsolutions.co.za - info@dza.kyocera.com

KYOCERA Document Solutions Inc. - 2-28, 1-Chome - Tamatsukuri Chuo-Ku - Osaka 540-8585 - Japan www.kvoceradocumentsolutions.com

\* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



<sup>\*\*</sup> Depending on the country